PETROTM OIL

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name **LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID A TYPE A**
Product Code(s) 04104/1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Automatic transmission fluids
Uses advised against Any other purpose.

1.3. Details of the supplier of the safety data sheet

Supplier

JLT 20th Floor
Fortune Executive Tower
Cluster T
Dubai, UAE
www.lubenzlubricants.com

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or

mixture Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [GHS]

2.2. Label Elements

Signal Word
None

Hazard Statements

EUH210 - Safety data sheet available on request

2.3. Other hazard

No information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances / 3.2. Mixtures

This product is a mixture. Health hazard information is based on its ingredients

Chemical Name	EC-No	CAS-No	Weight %	Classification (Reg. 1272/2008)	REACH Registration Number
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	-	50% - 100%	Asp. Tox. 1 (H304) (EUH066)	-
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	2.5% - 10%	**	-
Methacrylate copolymer	-	NOT AVAILABLE	1% - 2.5%	Eye Irrit. 2 (H319)	no data available

Additional information
Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.
See Section 15 for additional information on base oils.
**. Substances for which there are Community workplace exposure limits.

Full text of H- and EUH-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice — If symptoms persist, call a physician.

Inhalation — Move to fresh air.

Skin contact — Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use.

Eye contact — Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.

Ingestion — Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice.

Protection of First-aiders — Use personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Main Symptoms — None

4.3. Indication of immediate medical attention and special treatment needed

Notes to physician — Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:, Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons
Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture Special Hazard
Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). In the event of fire and/or explosion do not breathe fumes. This material creates a fire hazard because it floats on water. Combustible material.

Hazardous Decomposition Products
Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation.

Advice for non-emergency personnel Material can create slippery conditions.

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

6.4. Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials
Oxidizing agents

7.3. Specific end uses

Recommended use Automatic transmission fluids

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	The United Kingdom	France	Spain
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)				VLA-EC: 10 mg/m3 VLA-ED: 5 mg/m3
Highly refined base oil (Viscosity >20.5 cSt @40°C)				VLA-EC: 10 mg/m3 VLA-ED: 5 mg/m3

Chemical Name	Austria	Switzerland	Poland	Ireland
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)				STEL: 10 mg/m3 TWA: 5 mg/m3 (Mist)
Highly refined base oil (Viscosity >20.5 cSt @40°C)				STEL: 10 mg/m3 TWA: 5 mg/m3 (Mist)

Chemical Name	Finland	Denmark	Norway	Sweden
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5mg/m3 (Öljysumu)	TWA: 1 mg/m3 (Olietåge)	TWA: 1 mg/m3 (Oljetåke)	LLV: 1 mg/m3 STV: 3 mg/m3 (Oljedimma)
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5mg/m3 (Öljysumu)	TWA: 1 mg/m3 (Olietåge)	TWA: 1 mg/m3 (Oljetåke)	LLV: 1 mg/m3 STV: 3 mg/m3 (Oljedimma)

Derived No Effect Level (DNEL)

Workers Systemic toxicity

Workers Local effects

Consumers Systemic toxicity

Consumers Local effects

Predicted No Effect Concentration (PNEC)

8.2. Exposure controls

Engineering Measures	Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye Protection	Safety glasses with side-shields.
Hand Protection	Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.
Skin and body protection	Long sleeved clothing.
Respiratory protection	No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Hygiene measures	Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.
Environmental Exposure Controls	No special environmental precautions required.
Thermal hazards	None under normal use conditions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state @20°C	liquid	**Appearance**	clear amber
Odor	Hydrocarbon-like	**Odor Threshold**	Not Applicable

Property	Values	Note
pH	No information available.	
Melting/freezing point	No information available	
Boiling point/boiling range	No information available	
Flash Point	176 °C / 349 °F	
Evaporation rate	No information available	ASTM D 92

Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit	No information available	
lower flammability limit	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	0.8614	@15°C
Solubility(ies)	Insoluble in water	
Partition coefficient: n-octanol/water	Not Applicable	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Viscosity, kinematic	35.2 cSt @ 40 °C	ASTM D 445
Explosive properties	Not Applicable	
Oxidizing Properties	Not Applicable	

9.2 Other information

Viscosity, kinematic (100°C)	7.24 cSt @ 100°C	ASTM D 445
Pour point	-39 °C / -38 °F	ASTM D 97
VOC Content	No information available	

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition

10.5. Incompatible Materials

Oxidizing agents

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information - Principle Routes of

Exposure Inhalation None known

Eye contact None known

Skin contact None known

Ingestion None known

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known information.

Acute toxicity - Component Information

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	

Skin corrosion/irritation None known.
Serious eye damage/eye irritation None known.
Sensitization
Respiratory Sensitization None known.
Skin sensitization None known.

Germ Cell Mutagenicity None known.

Carcinogenicity None known.

Repeated Dose Toxicity None known.

Reproductive toxicity None known.

Specific target organ systemic toxicity (single exposure) None known

Specific target organ systemic toxicity (repeated exposure) None known.

Aspiration hazard None known.

PETROTM OIL

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects No special environmental measures are necessary.

12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

The product is insoluble and floats on water

12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products Dispose of in accordance with local regulations

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.

Other Data According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

Not regulated

14.2. UN proper shipping name

Not regulated

14.3. Transport hazard class

Not regulated

14.4. Packing group

Not regulated

14.5. Environmental Hazards

None

14.6. Special precautions for users

None

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

IMDG/IMO Not regulated

ADR/RID Not regulated

ICAO/IATA Not regulated

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008)
Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487081-40-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx

Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx
White mineral oil (petroleum)	8042-47-5	232-455-8	

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487067-30-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx

Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx

Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1	01-2119486452-34-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx

15.2. Chemical Safety Assessment

No information available

SECTION 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Repr.-Reproduction toxicity
Asp. Tox. - Aspiration Toxicity
Acute Tox. - Acute Toxicity
Aquatic Acute - Acute Aquatic Toxicity
Aquatic Chronic - Chronic Aquatic
Toxicity Eye Dam. - Eye Damage
Eye Irrit. - Eye Irritation
Skin Corr. - Skin Corrosion
Skin Irrit. - Skin Irritation
Skin Sens. - Skin
Sensitizer
Resp. Sens. - Respiratory Sensitizer
STOT SE - Specific target organ systemic toxicity (Single exposure)
STOT RE - Specific target organ systemic toxicity (repeated exposure) VOC - Volatile organic compounds

Full text of H-Statements referred to under sections 2 and 3

- H224 - Extremely flammable liquid and vapor
- H225 - Highly flammable liquid and vapor
- H226 - Flammable liquid and vapor
- H270 - May cause or intensify fire; oxidizer
- H271 - May cause fire or explosion; strong oxidizer
- H272 - May intensify fire; oxidizer
- H290 - May be corrosive to metals
- H300 - Fatal if swallowed
- H301 - Toxic if swallowed
- H302 - Harmful if swallowed
- H304 - May be fatal if swallowed and enters airways
- H310 - Fatal in contact with skin
- H311 - Toxic in contact with skin
- H312 - Harmful in contact with skin
- H314 - Causes severe skin burns and eye damage
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H318 - Causes serious eye damage
- H319 - Causes serious eye irritation
- H330 - Fatal if inhaled
- H331 - Toxic if inhaled
- H332 - Harmful if inhaled
- H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 - May cause respiratory irritation
- H336 - May cause drowsiness or dizziness
- H341 - Suspected of causing genetic defects
- H350 - May cause cancer
- H351 - Suspected of causing cancer
- H360 - May damage fertility or the unborn child
- H361 - Suspected of damaging fertility or the unborn child
- H362 - May cause harm to breast-fed children
- H370 - Causes damage to organs
- H371 - May cause damage to organs
- H372 - Causes damage to organs through prolonged or repeated exposure
- H373 - May cause damage to organs through prolonged or repeated exposure
- H400 - Very toxic to aquatic life
- H410 - Very toxic to aquatic life with long lasting effects
- H411 - Toxic to aquatic life with long lasting effects
- H412 - Harmful to aquatic life with long lasting effects
- H413 - May cause long lasting harmful effects to aquatic life
- H360Df - May damage the unborn child. Suspected of damaging fertility
- H360D - May damage the unborn child
- H360FD - May damage fertility. May damage the unborn child
- H360F - May damage fertility
- H361d - Suspected of damaging the unborn child
- H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child
- H361f - Suspected of damaging fertility
- EUH066 - Repeated exposure may cause skin dryness or cracking
- EUH210 - Safety data sheet available on request

Exposure scenario
No information available

Issuing Date: 11-27-2014
Revision Date: 11-27-2014

Revision Note Not Applicable.

DisclaimerThe information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text