



LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D IV

DESCRIPTION

LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D IV is universal ATF for the latest generation of automatic transmission formulated from hydro cracking oils and PAO with special additives and inhibition to ensure the proper operation of the automatic transmission.

APPLICATIONS

LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D IV was developed for use in automatic transmission, especially for Toyota and Aisin AW.

LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D IV Fluid can replace T, T-II and T-III Fluids.

It is advisable to flush with **LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D IV** before filling with **LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID D IV**

PRODUCT BENEFITS

- Guarantees maximum wear protection in all operating conditions
- Very good lubricating properties also at low temperatures in winter
- Protection against wear, corrosion and foaming
- Neutral behavior by inhibition to non-ferrous metals
- Excellent friction and anti-shudder performances
- Excellent viscosity stability in operation
- Excellent smooth shift action
- High, stable viscosity index
- Very low pour point
- Excellent oxidation stability
- Excellent durability thanks to its high quality base oils and additives
- Neutral behavior towards sealing materials
- Long fluid life based on excellent oxidation resistance
- Compatibility with synthetic rubber seal materials
- Resistance to foaming

RECOMMENDATIONS / SPECIFICATIONS

Fulfills the requirements for automatic transmission of Toyota and Aisin AW, Aisin Warner Automatic Gearbox, BMW 83 22 7 542 290 for MINI 6-Speed Aisin F21, 83 22 0 402 413 für MINI 6-Speed, Aisin F21 (nur USA), FORD 1327936, WSS-M2C924-A, XT-8QAW, General Motors 9986195, OPEL/GM 1940771, 1940774, Land Rover LR002748 6-Speed Aisin F21, RENAULT 7711218368 SU1 Gear, 7711172225 für Getriebe SU0 und SU1, TOYOTA JWS 3309, 08886-81016, 00279-000T4, 08886-01705, VOLVO 1161540, VW/AUDI G 055 025 A2, NISSAN 999MP-MTK00P für RE5F22A (Aisin AW55-50SN Nissan Altima, Maxima, Quest, Sentra), Matic K, Mazda K020-W0-049, b 99000-22800-001, ESSO JWS3317, Land Rover LR022460, Fiat 9.55550-AV1

TYPICAL TECHNICAL PROPERTIES

Color, VISUAL	RED
Density at 15°C, g/ml, ASTM D4052	0.8520
Kinematic Viscosity at 40°C, mm ² /s, ASTM D445	33
Kinematic Viscosity at 100°C, mm ² /s, ASTM D445	7.1
Viscosity Index, ASTM D2270	181
Flash Point(COC), °C, ASTM D92	208
Pour Point, °C, ASTM D97	-48
Brookfield viscosity at -40°C, mPa.s, ASTM D2983	13,000

Note: These characteristics are typical of current production. While future production will conform to LUBENZ specification, variations in these characteristics may occur.